

10.8V Brushless Full Auto Shut-off Cordless Angle Screwdriver & Wrench

SUMAKE
MAKE JOBS BETTER THAN EVER

Energy-Saving. Light Weight. Low Reaction Force.



Features

- High Accuracy: **CMK Value > 1.67 @ ±10%** according to ISO5393.
- High performance & powerful motor: New patented three-kinetic energy design to be supplied power by 10.8V (not 18V) and have less counterforce.

Torque value display
Comes with direct-displaying torque value design.

The 3rd Generation of patented brushless motor

Status indicating LED light
OK NG

Compact and reliable angle head

Duabile and precise shut-off clutch

Patent design with energy saving mode
Three adjustable phases to provide the most suitable fastening solutions and implement the best energy-saving design.

ECO: Energy saving mode.
(Suitable for hard joint fastening.)

Normal: General operating mode.
(Suitable for normal or medium joint fastening.)

Sport: Full speed & power mode.
(Suitable for soft joint fastening.)

Battery runtime comparison (2.5Ah) EAW-B1230A-25

- 530 times** (M6X17) at 30N-m
- 890 times** (M6X5.5) at 23N-m
- 1100 times** (M6X5.5) at 15N-m

LESS COUNTERFORCE

Light Weight
Only 1.5 kg (EAS-B1215-25)

BP1225L01
Li-ion Battery 10.8V 2.5Ah

BP1250L01
Li-ion Battery 10.8V 5.0Ah

BC10T01
Charger 10.8V-12V

Dimensions (Unit: mm):
 Head: 12, 28, 35, 11, 12, 14, 25, 33, 40, 68, 85, 93
 Body: 474, 492, 494, 512, 544
 Battery: 108, 108, 108, 108, 108

Model No. | Voltage | Free Speed (r.p.m) | Torque Range ±3% (Soft Joint) | Dimension (LxWxH) (mm) | Weight | Battery Pack | Charger | Bit Type

EAS-B1215A-25(50) EAW-B1230A-25(50)
EAW-B1250A-50 · EAW-B1260A-50

EAS-B1215A-25
EAS-B1215A-50

EAW-B1230A-25
EAW-B1230A-50

EAW-B1250A-50 · EAW-B1260A-50

Specification:

Model No.	Fastening Capacity	Voltage	Free Speed (r.p.m)			Torque Range ±3% (Soft Joint)		Dimension (LxWxH) (mm)	Weight		Battery Pack	Charger	Bit Type
			ECO	Normal	Sport	Nm	ft-lbs		(w/o Battery)	(w/ Battery)			
EAS-B1215CA-25	M4.5-M8.8	10.8V	250	380	500	2-15	1.48-11.06	474x72x108	1.3kgs (2.87lbs)	1.5kgs (3.31lbs)	BP1225L01 x 2 pcs	BC10T01	1/4"
EAW-B1230CA-25	M6.9-M11		175	260	350	8-30	5.90-22.13	492x72x108	1.63kgs (3.59lbs)	1.7kgs (3.75lbs)			3/8"
EAS-B1215CA-50	M4.5-M8.8		250	380	500	2-15	1.48-11.06	494x72x108	1.3kgs (2.87lbs)	1.7kgs (3.75lbs)	BP1250L01 x 2 pcs		1/4"
EAW-B1230CA-50	M6.9-M11		175	260	350	8-30	5.90-22.13	512x72x108	1.63kgs (3.59lbs)	1.9kgs (4.19lbs)			3/8"
EAW-B1250CA-50	M7.5-M12.8		125	190	250	10-50	7.38-36.88	544x72x108	2.4kgs (5.29lbs)	2.5kgs (5.51lbs)			1/2"
EAW-B1260CA-50	M8.8-M13.2		100	130	160	15-60	11.06-44.25	544x72x108	2.4kgs (5.29lbs)	2.5kgs (5.51lbs)			1/2"

*Remark: Standard tool with two batteries and battery charger.

XPET-C24-0129(R3)