

10.8V Brushless Full Auto Shut-off Cordless Screwdriver

Features

- High Accuracy: **CMK Value > 2.2 @ ±10%** according to ISO5393.
- High-quality heat-resistant brushless motor technology.



Torque value display
Comes with direct-displaying torque value design.

None-vibration bit sleeve design

Duabe and precise shut-off clutch

Front lamp for working position lighting

Patent design with energy saving mode
Three adjustable phases to provide the most suitable fastening solutions and implement the best energy-saving design.

ECO: Energy saving mode.
(Suitable for hard joint fastening.)

Normal: General operating mode.
(Suitable for normal or medium joint fastening.)

Sport: Full speed & power mode.
(Suitable for soft joint fastening.)

The 3rd Generation of patented brushless motor
The new generation of motor doubles the performance of the tool, increases work efficiency, and is more powerful.

Status indicating LED light

OK NG

Ergonomic design
Enhance comfortable feel.

BP1220L01
Li-ion Battery
10.8V 2.0Ah

BC10T01
Charger
10.8V-12V
A for UL plug
B for Europe plug
C for UK plug

700 times (M6X20) at 12N-m
1000 times (M6X20) at 8.4N-m
1400 times (M6X20) at 6N-m

Battery runtime comparison (2.0Ah) ES-B1212A-20

Sport Normal ECO

Specification:

Model No.	Fastening Capacity	Voltage (V)	Free Speed (r.p.m)			Torque Range (Soft Joint)			Dimension (LxW) (w/o Battery)	Weight	Battery Pack	Charger
			ECO	Normal	Sport	ft-lbs	Nm	Kgf/cm				
ES-B1205CA-20	M3.6-M6.0	10.8	750	1,130	1,500	0.74-3.69	1.0-5.0	10-51	190x190 mm	(w/o Battery) 1.0kgs (2.20lbs) (w/ Battery) 1.3kgs (2.60lbs)	BP1220L01 x 2 pcs	BC10T01
ES-B1207CA-20	M4.1-M6.4		660	920	1,200	1.11-4.79	1.5-6.5	15-66				
ES-B1209CA-20	M4.1-M7.3		550	800	1,000	1.11-6.64	1.5-9.0	15-92				
ES-B1212CA-20	M4.1-M8.0		150	230	300	1.11-8.85	1.5-12.0	15-122				
ES-B1212HCA-20	M4.5-M8.0		400	600	800	1.48-8.85	2.0-12.0	20-122				
ES-B1215CA-20	M4.1-M8.6		400	500	600	1.48-11.06	2.0-15.0	20-153				

*Remark: "A": w/ two Batteries ; w/o "A": one Battery

SUMAKE Industrial Co., Ltd.

4F, No.351, Yangguang St., Neihu District, Taipei, Taiwan, Zip:114-91
Tel: 886-2-2659-3500 Fax: 886-2-2659-3700
http://www.sumake.com e-mail: sales@sumake.com.tw



Certificate TW04/02301



XPET-C24-0129(R3)